

Small Drilling & Milling Center (Product No: Mx400)



Technical Parameters

Spindle type	Mechanical	Mechanical	High-speed
Max Spindle Speed	5000 rpm	9000 rpm	30000 rpm
Spindle Power	2.6 Kw 3.8 Kw	2.6 Kw	4.5 Kw
Spindle Taper	BT30		
Repeat positioning accuracy	±0.01 mm		
XAxis Travel	400 mm		
YAxis Travel	500 mm		
Z Axis Travel	200 mm		
Motor Power(X/Y)	0.75 Kw AC Servo		
Motor Power(Z)	1.2 Kw AC Servo		
Rapid feed rate(X/Y)	35000 mm/min		
Rapid feed rate(Z)	25000 mm/min		
Cutting feed rate	10000 mm/min		
ATC tool number	8		
Pneumatic supply	0.5 MPa		
Collet chuck	ER25		
Tool DIA. Range	1-16 mm		
Transmission	Taiwan Ball Screw		
Guide rail	Taiwan High-precision linear guide rail		
Table size	400*500 mm		
Max. Load	200 Kg		
Power supply	3 phase 380V		
N / G Weight	2000/2100 kg		
Machine Size	1400*1100*2000 mm		

4th axis (optional)Φ125 mmΦ170 mm

5 axis table (optional)Φ160 mm

YORNEW[®]

— — *Small CNC Machine* — —



Whats QR code

Yornew Automation Equipment Co., Ltd.

+86 757-25566186 +86 15916123639

manager@yornew.com

www.miumachine.com www.yornew.com

Phase 10, Tianfulai Hardware Park, No. 25, Xinfa Road, Ronggui, Shunde District, Foshan City, Guangdong, P.R.C.



Wechat QR code